



Revision Number: 003.0

Issue date: 08/21/2014

## 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product name:</b>	<b>LOCTITE AA H5004 B known as LOCTITE H5004 50ML PT B</b>	<b>IDH number:</b>	1387060
<b>Product type:</b>	Acrylic Adhesive	<b>Item number:</b>	1384596_1493268
<b>Restriction of Use:</b>	None identified	<b>Region:</b>	United States
<b>Company address:</b>	<b>Contact information:</b> Telephone: (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com		
Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067			

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**DANGER:** HIGHLY FLAMMABLE LIQUID AND VAPOR.  
 CAUSES SKIN IRRITATION.  
 MAY CAUSE AN ALLERGIC SKIN REACTION.  
 CAUSES SERIOUS EYE DAMAGE.  
 MAY CAUSE RESPIRATORY IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	2
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

### PICTOGRAM(S)



### Precautionary Statements

<b>Prevention:</b>	Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing vapors, mist, or spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.
<b>Response:</b>	If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Immediately call a poison control center or physician. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.
<b>Storage:</b>	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
<b>Disposal:</b>	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Methyl methacrylate	80-62-6	30 - 60
Aromatic methacrylate	10595-06-9	10 - 30
Methacrylic acid	79-41-4	5 - 10
Methacrylate Ester	Proprietary	5 - 10
2-Hydroxyethyl methacrylate	868-77-9	5 - 10
Cumene hydroperoxide	80-15-9	0.1 - 1
Polyglycol dimethacrylate	Proprietary	0.1 - 1

\* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

<b>Inhalation:</b>	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention.
<b>Skin contact:</b>	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. If symptoms develop and persist, get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
<b>Eye contact:</b>	Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding eyelids open all the time. Get medical attention.
<b>Ingestion:</b>	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
<b>Symptoms:</b>	See Section 11.

### 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Water spray (fog), foam, dry chemical or carbon dioxide.
<b>Special firefighting procedures:</b>	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
<b>Unusual fire or explosion hazards:</b>	Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back. Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
<b>Hazardous combustion products:</b>	Oxides of carbon. Toxic fumes. Irritating vapors.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	Do not allow product to enter sewer or waterways.
-----------------------------------	---

**Clean-up methods:**

Remove all sources of ignition. Ensure adequate ventilation. Wear appropriate personal protective equipment. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for disposal.

## 7. HANDLING AND STORAGE

**Handling:**

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. During use and until all vapors are gone: Keep area ventilated - do not smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources of ignition. Make sure containers are properly grounded before use or transfer of material. Keep container closed.

**Storage:**

Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Keep away from heat, spark and flame. Protect from direct sunlight. Maintain head space in storage containers to support oxygen requirements of the inhibitor(s).

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Methyl methacrylate	50 ppm TWA 100 ppm STEL (Sensitizer.)	100 ppm (410 mg/m <sup>3</sup> ) PEL	None	50 ppm
Aromatic methacrylate	None	None	None	None
Methacrylic acid	20 ppm TWA	None	None	None
Methacrylate Ester	None	None	None	None
2-Hydroxyethyl methacrylate	None	None	None	3 ppm Ceiling
Cumene hydroperoxide	None	None	1 ppm (6 mg/m <sup>3</sup> ) TWA (SKIN)	None
Polyglycol dimethacrylate	None	None	None	None

**Engineering controls:**

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

**Respiratory protection:**

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

**Eye/face protection:**

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

**Skin protection:**

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical state:**

Liquid

**Color:**

Light, Pink

**Odor:**

Characteristic

**Odor threshold:**

Not available.

**pH:**

Not available.

**Vapor pressure:**

Not available.

**Boiling point/range:**

Not available.

**Melting point/ range:**

Not available.

**Vapor density:**

Not available.

<b>Flash point:</b>	10 °C (50°F) Setaflash Closed Cup
<b>Flammable/Explosive limits - lower:</b>	Not available.
<b>Flammable/Explosive limits - upper:</b>	Not available.
<b>Autoignition temperature:</b>	Not available.
<b>Evaporation rate:</b>	Not available.
<b>Solubility in water:</b>	Not available.
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>VOC content:</b>	0.37 % (value as mixed for use)
<b>Viscosity:</b>	Not available.
<b>Decomposition temperature:</b>	Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable under normal conditions of storage and use.
<b>Hazardous reactions:</b>	May occur with excessive aging, excessive heat, polymerization catalyst, inhibitor depletion, direct sunlight and under oxygen-free atmospheres.
<b>Hazardous decomposition products:</b>	Oxides of carbon. Toxic fumes. Irritating vapors.
<b>Incompatible materials:</b>	Acids. Bases. Oxidizing agents. Reducing agents. Free radical initiators. Inert gases. Oxygen scavengers. Amines. Heavy metals. Peroxides. Mineral acids.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	Keep away from heat, ignition sources and incompatible materials. Protect from direct sunlight. Loss of polymerization inhibitor. Loss of dissolved air. Oxidizing conditions. Freezing conditions. Inert gas blanketing. Do not mix in batches greater than 100 grams (0.22 pounds) unless you plan to use immediately.

## 11. TOXICOLOGICAL INFORMATION

<b>Relevant routes of exposure:</b>	Skin, Inhalation, Eyes
-------------------------------------	------------------------

### Potential Health Effects/Symptoms

**Inhalation:** May cause respiratory tract irritation. Drowsiness. Dizziness.  
**Skin contact:** Causes skin irritation. May cause allergic skin reaction.  
**Eye contact:** Causes serious eye damage.  
**Ingestion:** May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Methyl methacrylate	Oral LD50 (RAT) = 7,800 mg/kg Oral LD50 (RABBIT) = 6,000 mg/kg Oral LD50 (RAT) = 9,400 mg/kg Inhalation LC50 (RAT, 8 h) = 3750 ppm	Allergen, Irritant, Kidney, Liver, Mutagen, Nervous System, Respiratory
Aromatic methacrylate	None	Irritant, Allergen
Methacrylic acid	Oral LD50 (RABBIT) = 1,200 mg/kg Oral LD50 (RAT) = 1,060 mg/kg Oral LD50 (RAT) = 2,224 mg/kg Dermal LD50 (RABBIT) = 500 mg/kg Inhalation LC50 (RAT, 4 h) = 7.1 mg/l	Corrosive, Irritant, Allergen
Methacrylate Ester	None	Irritant, Allergen
2-Hydroxyethyl methacrylate	Oral LD50 (RAT) = 11.2 g/kg Oral LD50 (RAT) = 5,050 mg/kg	Irritant, Allergen
Cumene hydroperoxide	None	Allergen, Central nervous system, Corrosive, Irritant, Mutagen
Polyglycol dimethacrylate	None	Irritant, Allergen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Methyl methacrylate	No	No	No
Aromatic methacrylate	No	No	No
Methacrylic acid	No	No	No
Methacrylate Ester	No	No	No
2-Hydroxyethyl methacrylate	No	No	No
Cumene hydroperoxide	No	No	No
Polyglycol dimethacrylate	No	No	No

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:** D001: Ignitable.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Adhesives  
**Hazard class or division:** 3  
**Identification number:** UN 1133  
**Packing group:** II  
**DOT Hazardous Substance(s):** alpha,alpha-Dimethylbenzylhydroperoxide, Methyl methacrylate

**International Air Transportation (ICAO/IATA)**

Proper shipping name: Adhesives  
Hazard class or division: 3  
Identification number: UN 1133  
Packing group: II

**Water Transportation (IMO/IMDG)**

Proper shipping name: ADHESIVES  
Hazard class or division: 3  
Identification number: UN 1133  
Packing group: II

**15. REGULATORY INFORMATION****United States Regulatory Information**

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

**TSCA 12 (b) Export Notification:** None above reporting de minimis

**CERCLA/SARA Section 302 EHS:** None above reporting de minimis  
**CERCLA/SARA Section 311/312:** Fire, Immediate Health, Delayed Health  
**CERCLA/SARA Section 313:** This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Methyl methacrylate (CAS# 80-62-6). Aromatic methacrylate (CAS# 10595-06-9).

**CERCLA Reportable quantity:** Methyl methacrylate (CAS# 80-62-6) 1,000 lbs. (454 kg)  
Cumene hydroperoxide (CAS# 80-15-9) 10 lbs. (4.54 kg)

**California Proposition 65:** This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

**Canada Regulatory Information**

**CEPA DSL/NDSL Status:** Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

**16. OTHER INFORMATION**

**This safety data sheet contains changes from the previous version in sections:** New Safety Data Sheet format.

**Prepared by:** Rena Petrides, Regulatory Affairs Specialist

**Issue date:** 08/21/2014

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.